

**CAUTION:**

Work on top of a roof requires extreme caution. If you are not qualified to do this installation, we recommend that you consult a professional builder.

TYPICALLY, BRACKETS SHOULD ALTERNATE ONTO OPPOSING SLOPES.

1/4-20 NUT & BOLT  
(PROVIDED)

ROOF RIDGE  
LINE

ASPHALT SHINGLE ROOF OR EQUAL

ROOF CRESTING (1/4" THICK SHOWN)

METAL BRACKET  
2-1/2" X 2 1/2" X 5/8" X 1/8"  
(NATIONAL N 266-482 STANDARD)

PRE-DRILLED HOLES  
(FASTENERS BY OTHERS)

ANGLE VARIES  
TO REQUIREMENTS

THIS DRAWING IS NOT DRAWN TO SCALE

THIS DRAWING IS AN INSTRUMENT OF PROFESSIONAL SERVICE AND SHALL REMAIN THE PROPERTY OF ARCHITECTURAL IRON COMPANY WHETHER THE PROJECT FOR WHICH IT IS PREPARED IS EXECUTED OR NOT. NO CHANGES, ALTERATIONS, ADDITIONS, OR DELETIONS MAY BE MADE EXCEPT BY ARCHITECTURAL IRON COMPANY. THIS DRAWING SHALL NOT BE REPRODUCED BY ANYONE ON OTHER PROJECTS, FOR ADDITIONS TO THIS PROJECT, OR FOR COMPLETION OF THIS PROJECT BY OTHERS WITHOUT WRITTEN CONSENT.

This drawing is available in AutoCad format.

**Note:**

This cresting bracket is customized during fabrication to match the angle of the roof slope of which it is being installed upon.

**AIC**

**Architectural Iron Company**

104 Ironwood Court  
Milford, PA 18337

800-442-IRON /4766

Fax: 570-296-IRON /4766

www.architecturaliron.com

E-mail: info@architecturaliron.com

**STANDARD CRESTING MOUNTING BRACKET**

Drawing No.  
266-482

Drafted By:  
W.A./J.W.

Checked By:  
D.Q.

Date:  
07/08/02

Part Number  
266-482